

PARTNER

CARE . TRUST . RESPONSIBILITY

All-in-One Touch POS Terminal PT-6212

All you need



The All-in-One Touch POS Terminal PT-6212 is a perfect solution for small and medium-size enterprises to keep pace with competitors. The POS Terminal comes with integrated customer display, 80mm Epson thermal printer and 3track MSR as standard. Further components like Addimat/Dallas lock, RFID or 2nd screen can be built in as an option.

Its compact and small footprint design makes the device extremely counter-space saving. Furthermore the attractive and at the same time inconspicuously appearance fits into every POS environment. Without any extra modules, cables etc. it is easy to install and can be used in many different businesses like retail, kiosk, convenience-stores, fashion or hospitality.

Special Features:

- Elegant, compact and fanless design
- 12.1" TFT-LCD touch screen
- Open architecture
- Modular design for easy maintenance
- Integrated 3-track MSR
- 80 mm Epson thermal printer
- 2x20 VFD customer display

Optional:

- Solid State Drive
- RAID
- RFID module
- WiFi module

All-in-One Touch POS Terminal PT-6212

Technical data

Item	PT-6215									
CPU	Intel Atom N270 @ 1.6GHz/512K L2 Cache									
Chipset	Intel 945GSE + ICH7M									
Memory	System chips with DDR2 1GB std, support up to 2GB									
LCD	12.1" TFT-LCD									
Resolution	1024 x 768									
Touch	5-wire resistive touch									
LCD Brightness	250 cd/m ² (w/o touch)									
LAN	10/100/1000Mbps on board Ethernet controller									
Storage	SATA 3.5" HDD or optional SATA SSD									
I/O ports	4 x COM ports 1 x RJ11 port (+24V) 1 x PS/2 Keyboard port 1 x RJ-45 LAN port 5 x USB ports 1 x DC +12V 1 x VGA port									
Operation System	WEPOS / POSReady / Windows XP Pro / Windows XP embedded / Windows 7 / Linux									
Power Supply	AC 100V~240V / DC12V / 12.5A 150 watt power adaptor									
Environment	<table border="1"> <thead> <tr> <th></th> <th>Operating</th> <th>Storage</th> </tr> </thead> <tbody> <tr> <td>Temperature</td> <td>0~40 °C</td> <td>C -20~60 °C</td> </tr> <tr> <td>Humidity</td> <td>15% ~ 80%</td> <td>15% ~ 80%</td> </tr> </tbody> </table>		Operating	Storage	Temperature	0~40 °C	C -20~60 °C	Humidity	15% ~ 80%	15% ~ 80%
	Operating	Storage								
Temperature	0~40 °C	C -20~60 °C								
Humidity	15% ~ 80%	15% ~ 80%								
Dimension	328 mm (W) x 295,5 mm (D) x 246,8 mm (H)									
Integrated Peripherals	3-Track MSR, 2 x 20 VFD customer display, 80 mm Thermal Epson printer with auto cutter									
Options	Solid State Drive, RAID, RFID module, WiFi module									



12.1" TFT-LCD Touch Screen



3-Track MSR



80mm Epson Thermal printer with Auto Cut and Paper Feed



Rear VFD Customer Display



Compact and small footprint



Modular design for easy maintenance